MATERIAL SAFETY DATA SHEET

BIRCHWOOD CASEY® TRU-OIL®

Page 1 of 4 DATE REVISED: 6/1/07 REVISION MSDS NO. 3

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: BIRCHWOOD CASEY TRU-OIL®

PRODUCT PART NUMBERS: 23123, 23035, 23150, TO22, TO8, TO

MANUFACTURED BY: BIRCHWOOD LABORATORIES, INCORPORATED

7900 Fuller Road

Eden Prairie, MN 55344 USA

Product Information Telephone Number: (952) 937-7900 (8:00-4:00pm CST)

Fax Number: (952) 937-7979 www.birchwoodcasey.com

24 HOUR TRANSPORTATION EMERGENCY NUMBER: CHEMTREC 800-424-9300 U.S. & CANADA

703-527-3887 INTERNATIONAL (Collect)

24 HOUR POISON CONTROL EMERGENCY NUMBER: 866-291-7152 U.S. & CANADA

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: **DANGER! Harmful or fatal if swallowed. Combustible liquid and vapor.** Keep away from sparks and open flames. Cans involved in fire may explode. Irritating to eyes, skin, upper respiratory tract.

APPEARANCE/ODOR: Opaque, light brown liquid with solvent odor

EYE CONTACT: Irritation upon direct contact. Symptoms may include stinging, tearing, redness and swelling.

SKIN CONTACT: Mildly irritating. Prolonged or repeated skin contact can result in defatting, drying of the skin with symptoms of redness, stinging.

INGESTION: Irritation to the gastrointestinal tract. This material can enter the lungs during swallowing or vomiting and cause lung damage.

INHALATION: Inhalation may cause irritation to the respiratory tract (nose, throat and lungs). Inhalation of high vapor concentrations may cause central nervous system effects, and symptoms such as headache, dizziness, disorientation.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Description	CAS#	Weight	OSHA PEL*	OSHA PEL	ACGIH TLV	ACGIH TLV
		%	TWA	STEL/C	TWA	STEL/C
Mineral Spirits**	8052-41-3	> 56	500 ppm	NE	100 ppm	NE
Modified Oil	Proprietary	< 33	NE	NE	NE	NE
Linseed Oil***	Proprietary	< 11	$15 \text{ mg/m}^{3(\text{total})};$	NE	10 mg/m^3	NE
			5 mg/m ^{3(resp)}			

TWA – Time-weighted Average STEL – Short-term exposure limit C – Ceiling

(skin) – skin designation means that harmful amounts may be absorbed through the skin

NE = not established NA = not applicable NDA = no data available

^{*} Certain States enforce PELs that were in place in 1989, but were later removed by the U.S. Supreme Court. Check with your State OSHA to determine which PEL is enforced in your State.

^{**} OELs as Stoddard Solvent

^{***} OELs as vegetable oil mist

Page 2 of 4 DATE REVISED: 6/1/07 REVISION MSDS NO. 3

4. FIRST AID MEASURES

EYE CONTACT: Flush immediately with clean water. Continue for at least 15 minutes. Seek medical attention if necessary.

SKIN CONTACT: Remove contaminated clothing to avoid prolonged contact. Wash affected areas with water. Seek medical attention if irritation develops.

INGESTION: Call Poison Control Center immediately. Do not induce vomiting. If victim is conscious, give 1-2 glasses of water.

INHALATION: Remove from exposure. Seek medical attention if necessary if breathing is difficult. Seek medical attention if symptoms of overexposure develop or persist.

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES

FLASHPOINT: 111 °F METHOD USED: Closed Cup

FLAMMABLE LIMITS: LFL: 1.0 % UFL: 6.0 %

EXTINGUISHING MEDIA: Foam, dry chemical, carbon dioxide or any Class B extinguishing agent. Water may be unsuitable as an extinguishing medium, but helpful in keeping adjacent containers cool.

FIRE & EXPLOSION HAZARDS: Vapors may form an explosive mixture in air. Closed containers may rupture when exposed to extreme heat.

SPECIAL FIRE FIGHTING PROCEDURES: Firefighters should wear approved SCBA and full turn-out gear.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Wear recommended protective equipment. Remove all sources of ignition. Ventilate area. Absorb spill with an absorbent material such as sawdust, vermiculite or sand and place material into a closed container. Prevent material from entering water systems or sewers.

Review current local, state and federal laws, codes, statutes, and regulations to determine appropriate agencies to be notified, and the conditions under which they are to be notified. (See Section 13 for waste disposal comments).

7. HANDLING AND STORAGE

HANDLING: Avoid breathing vapors. Avoid eye and skin contact. Prohibit smoking in the area and exclude sources of spark or open flame. Avoid static discharge. Wear protective equipment when handling product. Empty containers may still have product residue and flammable vapors. Avoid spontaneous combustion of contaminated rags and other easily ignitable accumulations (such as spray booth residues) by immediate immersion in water. Keep out of the reach of children.

STORAGE: Do not store where temperature may exceed 120°F

8. EXPOSURE CONTROL / PERSONAL PROTECTION

RESPIRATORY PROTECTION: Use a NIOSH approved respirator (Full or half-face organic vapor/P95 cartridge type) if any of the occupational exposure limits in Section 3 may be exceeded.

EYE PROTECTION: safety glasses with side shields, or goggles

PROTECTIVE GLOVES / BODY PROTECTION: polyvinyl alcohol (PVA) or natural rubber

Page 3 of 4 DATE REVISED: 6/1/07 REVISION MSDS NO. 3

VENTILATION: Use general/dilution or local exhaust ventilation as needed to ensure that occupational exposure limits are not exceeded. Do not use in enclosed spaces.

OTHER PROTECTIVE EQUIPMENT: Eyewash

NOTE: All PPE should be selected on the basis of an exposure assessment performed by a competent person.

9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: > 315°F SPECIFIC GRAVITY: (Water = 1): 0.825

VAPOR PRESSURE: NDA VOLATILE BY VOLUME: 60%

VAPOR DENSITY: (Air = 1): > 1 EVAPORATION RATE: (Ethyl Ether = 1): < 1

SOLUBILITY IN WATER: Immiscible pH: NA

APPEARANCE: Brown liquid ODOR: solvent odor

10. STABILITY AND REACTIVITY

STABILITY: Stable.

CONDITIONS TO AVOID: Avoid high temperatures (> 120 °F) and ignition sources.

INCOMPATIBILITY (materials to avoid): Strong oxidizers

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition may produce carbon monoxide, carbon dioxide,

sulfur oxides

HAZARDOUS POLYMERIZATION: Will not occur.

11. TOXICOLOGICAL INFORMATION

There is no product based toxicological information for this product. Toxicology information is provided for ingredients.

LD₅₀: NDA

TARGET ORGANS: Eyes, skin, lungs (irritant), liver, kidney, CNS.

Medical conditions that may be aggravated by exposure: Pre-existing skin, eye, respiratory, CNS disorders.

Carcinogenicity: IARC: None NTP: None OSHA: None

12. ECOLOGICAL INFORMATION

ECOTOXICITY: NDA

ENVIRONMENTAL FATE: NDA

13. DISPOSAL CONSIDERATIONS

If discarded, this material and containers should be treated as hazardous wastes based on the characteristic of ignitability as defined under federal RCRA regulations (40 CFR 261). Review current local, state and federal laws, codes, statutes and regulations to determine current status and appropriate disposal method for the ingredients listed in Section 2. Any disposal practice must be in compliance with local, state, and federal laws and regulations. Contact the appropriate agency for specific information. Treatment, transport, storage and disposal of hazardous waste must be dealt with by a licensed facility or waste hauler.

14. TRANSPORT INFORMATION

D.O.T. HAZARDOUS MATERIALS DESCRIPTION AND PROPER SHIPPING NAME:

Flammable Liquid, N.O.S (Naphtha, Petroleum) 3 / UN1993 / P.G. III. Exceptions: 49CFR 173.150

15. REGULATORY INFORMATION

TSCA (TOXIC SUBSTANCES CONTROL ACT): the materials in this product are listed on the TSCA Inventory. CERCLA (Comprehensive Response compensation and Liability Act, 40 CFR 117, 302: Reportable Quantities: NDA

SARA TITLE III (Superfund Amendments and Authorization Act):

Section 311/312:

Immediate Health Effects: Yes Delayed Health Effects: Yes

Fire Hazard: Yes

Sudden Release of Pressure Hazard: No

Reactivity Hazard: No

Section 313 Reportable Ingredients: None

STATE "RIGHT-TO-KNOW": This product may contain components cited on certain state lists. Consult with your individual State regarding this product's components.

16. OTHER INFORMATION

National Fire Protection Association (NFPA): Health: 2 Flammability: 2 Reactivity: 0

The data here is for hazard communication to our employees, our customers and their employees, and authorized regulatory agencies. For the intended purpose, this MSDS (Material Safety data Sheet) may be duplicated or the data transcribed to an alternative form.

<u>NOTE</u>: The information contained herein is provided in good faith and is believed to be correct as of the date hereof. However, Birchwood Laboratories, Inc. makes no representation as to the comprehensiveness or accuracy of the information. It is expected that individuals receiving the information will exercise their independent judgment in determining its appropriateness for a particular period.

Accordingly, Birchwood Laboratories, Inc. will not be responsible for damages of any kind resulting from the use of or reliance upon such information. NO REPRESENTATIONS, OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER NATURE ARE MADE HEREUNDER TO WHICH THE INFORMATION REFERS. The responsibility to provide a safe workplace remains with the user. The user should consider the health hazards and safety information contained herein as a guide and should take those precautions required in an individual operation to instruct employees and develop work practice procedures for a safe work environment.

FOR ASSISTANCE WITH PLACING ORDERS:

- Product Pricing / Payment Terms
- Shipping and Tracing of Shipments
- Sales Rep Locations

Call our Sales Department (952) 937-7933

Or 1-800-328-6156 or Fax (952) 937-7979

FOR PRODUCT USAGE ASSISTANCE

- Questions on Operation of Products
- Solving Finishing Problems
- · Operator Safety and Pollution Control

Call our Customer Service Desk (952) 937-7916

Or 1-800-328-6156 or Fax (952) 937-7979